



PART NUMBER CODING

MMT-XX

B

X

- Contact Plating
 G0:Gold Flash
 G1:3U*Gold
 G2:5U*Gold
 G3:10U*Gold
 G4:15U*Gold
 G5:20U*Gold
 G6:30U*Gold
 S0:Gold Flash/Tin
 S1:3U*Gold/Tin
 S2:5U*Gold/Tin
 S3:10U*Gold/Tin
 S4:15U*Gold/Tin
 S5:20U*Gold/Tin
 S6:30U*Gold/Tin
 SN:Tin

- Material
 B=Brass
 P=Phosphor Bronze

- TYPE:
 1=TYPE1
 2=TYPE2



Tel:+86 769 82581808 FAX:+86 769 81766192
 E-Mail:winpin@win-pin.com Http:www.win-pin.com

NOTES:
 Current Rating: 1.0AMP
 Withstand Voltage:500V AC/DC
 Contact Resistance:20mΩ Max
 Insulation Resistance:5000MΩ Min
 Operation Temperature:-25°C to +85°C

Contact Material:Phosphor Bronze
 Contact Plating:TIN

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN METRIC TOLERANCES ARE:
 DECIMALS Angle
 X.X:±0.40 ± 3°
 X.XX:±0.25
 X.XXX:±0.15

PART NO: MMT-XXBX

TITLE: Micro Match CRIMP TERMINAL

SCALE	1:1
UNIT	MM
PROJ.	
SHEET	

A0	2015/06/25	NEW	Hua.ZT		Hua.ZT
REV	DATE	MODIFICATION DESCRIPTIO	DRAW	CHANGE	APPROVE