



PART NUMBER CODING

MMMI-XX XX X X 1

No. of Pins
4-26

Contact Plating
SN: Bright Tin
MS: MATT Tin

Colour
A= purplish red 紫红
B= Red 红色

Packing
B= PE Bag
T= Tube

Pins	Dim A	Dim B	Q'ty/ Tube
04	2.54	8.45	67
06	5.08	10.99	52
08	7.62	13.53	42
10	10.16	16.07	36
12	12.70	18.61	31
14	15.24	21.15	27
16	17.78	23.69	24
18	20.32	26.23	22
20	22.86	28.77	20
22	25.40	31.31	18
24	27.94	33.85	17
26	30.48	36.39	16



Tel: +86 769 82581808
E-Mail: sales@winpin.net

FAX: +86 769 81766192
Http: www.winpin.net

PART NO: MMMI-XXXXXX1

TITLE: Micro Mini DIP Plug (IDC TYPE)

NOTES:

Rating Current: 1.0AMP
Withstand Voltage: 500V AC/DC
Contact Resistance: 20mΩ Max
Insulation Resistance: 1000MΩ Min
Operation Temperature: -40°C to +105°C

MATERIAL:

Contact: Phosphor Bronze
Contact Plating: Sn over Ni
Insulator: PBT (UL94V-0)

UNLESS OTHERWISE
SPECIFIED DIMENSIONS
ARE IN METRIC

TOLERANCES ARE:
DECIMALS Angle
X.X: ±0.40 ± 3°
X.XX: ±0.25
X.XXX: ±0.15

SCALE	1:1
UNIT	MM
PROJ.	
SHEET	

Recommended P.C.B Layout (Top Side) (PCB BOARD TOLERANCE ±0.05)

