





PART NUMBER CODING

MPEM28-1 XX XX X 101 X X


No. of Pins	Contact Plating	Insulator Material/Colour	Packing	Series
02-40pin	G0:Gold Flash G1:3U*Gold G2:5U*Gold G3:10U*Gold G4:15U*Gold G5:20U*Gold G6:30U*Gold S0:Gold Flash/Tin S1:3U*Gold/Tin S2:5U*Gold/Tin S3:10U*Gold/Tin S4:15U*Gold/Tin S5:20U*Gold/Tin S6:30U*Gold/Tin SN:Tin	A:PPS/Black	A:Tray B:PE Bag T:Tube	1=TYPE1 2=TYRE2






Type 1



Type 2



Recommended P.C.B Layout(Top Side) (PCB BOARD TOLERANCE+0.05)



Tel: +86 769 82581808 FAX: +86 769 81766192
E-Mail: sales@winpin.net Http: www.winpin.net

PART NO: MPEM28-1XXXXX101XX

TITLE: 2.00mm Machined Pin Header Single Row 180°SMT H=2.8 L=10.1

NOTES:
Current Rating: 2.0AMP
Contact Resistance: 10mΩ Max
Withstand Voltage: 1000V AC/DC
Mechanical Life: Min 500 cycles
Connecting Pin: Ø0.50mm
Operation Temperature: -40°C to +105°C

Material:
Sleeve: Brass
Contact Plating: Au or Sn over Ni
Insulator Material: PPS(UL94V-0)

UNLESS OTHERWISE
SPECIFIED DIMENSIONS
ARE IN METRIC
TOLERANCES ARE:
DECIMALS
X.X: ±0.40
X.XX: ±0.25
X.XXX: ±0.15

SCALE	1:1
UNIT	MM
PROJ.	
SHEET	

A0	2015/06/25	NEW	Huan.Tan		Huan.Tan
REV	DATE	MODIFICATION DESCRIPTIO	DRAW	CHANGE	APPROVE