

HSF Pb RoHS

Recommended P.C.B Layout(Top Side)
(PCB BOAR TOLERANCE±0.05)







PART NUMBER CODING

MPFS30-2 XX XX X 119 X 1

- No.of Pins: 01-40pin
- Contact Plating: G0:Gold Flash; G1:3U"Gold; G2:5U"Gold; G3:10U"Gold; G4:15U"Gold; G5:20U"Gold; G6:30U"Gold; S0:Gold Flash/Tin; S1:3U"Gold/Tin; S2:5U"Gold/Tin; S3:10U"Gold/Tin; S4:15U"Gold/Tin; S5:20U"Gold/Tin; S6:30U"Gold/Tin; SN:Tin
- Insulator Material/Colour: A:PPS/Black
- Packing: A:Tray; B:PE Bag; T:Tube





WINPIN

WINPIN
Tel:+86 769 82581808 FAX:+86 769 81766192
E-Mail:sales@winpin.net Http:www.winpin.net

PART NO: MPFS30-2XXXXX119X1

TITLE: 2.54mm Machined Pin Header Dual Row 180° H=3.00 L=11.96

NOTES:
Current Rating:.3.0AMP
Contact Resistance:10mΩ Max
Withstand Voltage:1000V AC/DC
Mechanical Life:Min 500 cycles
Connecting Pin:Ø0.60/Ø0.50mm
Operation Temperature:-40℃ to +105℃

Material:
Sleeve:Brass
Contact Plating:Au or Sn over Ni
Insulator Material:PPS(UL94V-0)

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN METRIC
TOLERANCES ARE:
DECIMALS Angle
X.X:±0.40 ± 3°
X.XX:±0.25
X.XXX:±0.15

SCALE	1:1
UNIT	MM
PROJ.	
SHEET	

REV	DATE	MODIFICATION DESCRIPTIO	DRAW	CHANGE	APPROVE
A0	2015/06/25	NEW	Nike.TAN	——	Andy